



DIMENSIONS



SPECIFICATIONS

HOUSING - Die-cast aluminum back housing with cast-in template for mounting over an electrical box. Color matched polycarbonate front housing with clear ribbed lens area. 1/2" coin plugs with o-ring for conduit and photocell. Textured architectural powder coat finish over a chromate conversion coating.

REFLECTOR - Aluminum reflector.

LENS - Clear ribbed polycarbonate lens area in front housing.

MOUNTING - Cast-in template for mounting directly over a 4" recessed outlet box, or use 1/2" surface conduit.

WATTAGE - Induction: 40W, 5000K.

FINISH - Available colors are bronze, black, white, and gray. Custom colors are available upon request (consult factory).

LISTINGS & RATINGS - CSA: Listed for wet locations.

ORDERING INFORMATION SELECT APPROPRIATE CHOICE FROM EACH COLUMN TO FORMULATE ORDER CODE. Refer to example below.

SERIES	DISTRIBUTION	LAMP WATTAGE	LIGHT SOURCE	LINE VOLTAGE	LUMINAIRE FINISH	ACCESSORIES
BRI	AR - Aluminum Reflector	40W	IND - Induction	120V 277V	BRZ - Bronze BLK - Black WHT - White GRY - Grey CC - Custom Color	NO - No Option

BRI **AR** **40** **IND** **120** **BRZ** **NO**

(EXAMPLE ORDER)

ORDER :

WLS-BRI _____

Approved By: _____ Project Name: _____

Location: _____ Date: _____

P.O. Box 100519 | Fort Worth, TX 76185 | www.wslighting.com

WLS LIGHTING SYSTEMS
Consider the Impact!