


WLS LIGHTING SYSTEMS

VNL SERIES SMALL LED CANOPY



DIMENSIONS



SPECIFICATIONS

HOUSING - Heavy-duty die-cast aluminum housing.

LENS - Injection molded polycarbonate lens with UV inhibitors. Silicon gasket eliminates moisture, dust and insect penetration.

FINISH - Textured architectural bronze powder coat finish over a chromate conversion coating is standard. Consult factory for available custom colors.

LIGHT SOURCE - Fully dimmable (analog or PWM) LED that features a long life (50,000 hrs), reliability, sustained image, uniform beam (intensity and color temperature - no yellow ring or color shadows) and color point consistency part to part and through life. Light emitting diode is fully enclosed providing an IP 66 rating.

MOUNTING - Universal operating position.

OPTICS - Possibilities include: sharp beam cut-off optics, very low profile spot and flood optics (<20mm) and adjustable beam shaping.

COLOR TEMPERATURE - Choice of color temperatures (2700k, 3000k and 4000k).



(PC1 & PC2) Photocell



Optic Options:
(2) 20° beam
(4) 40° beam
(6) 60° beam

ORDERING INFORMATION SELECT APPROPRIATE CHOICE FROM EACH COLUMN TO FORMULATE ORDER CODE. Refer to example below.

SERIES	TOTAL WATTS	BALLAST	COLOR TEMP	OPTICS	LUMINAIRE FINISH	OPTIONS
VNL	7.5* 15* 22** *40 LPW (Lumens Per Watt) **45 LPW (Lumens Per Watt)	Q - Quad Tap	2 - 2700k 3 - 3000k 4 - 4000k	N - None 2 - 20° 4 - 40° 6 - 60°	BRZ - Bronze CC - Custom Color	PC1 - 120V photocell PC2 - 277V photocell NO - No Option

VNL 15 Q 3 N BRZ NO

(EXAMPLE ORDER)

ORDER :

WLS-VNL

Approved By: _____ Project Name: _____

Location: _____ Date: _____

P.O. Box 100519 | Fort Worth, TX 76185 | www.wslighting.com

WLS LIGHTING SYSTEMS

Consider the Impact!