


WLS LIGHTING SYSTEMS

AOL SERIES

LED WALL / RECESSED



DIMENSIONS



SPECIFICATIONS

HOUSING - 15" diameter die cast aluminum housing & open top frame. 1/2" coin plug with o-rings for conduit & photocell.

REFLECTOR - White aluminum reflector.

LENS - Clear prismatic molded or frosted molded borosilicate glass lens.

FINISH - Textured powdercoat finish over a chromate conversion coating in Bronze, Black, or White.

MOUNTING - Cast-in template for mounting directly over a 4" recessed box, or use 1/2" surface conduit.

WATTAGE - 1 x 15w, 2 x 7.5w or 15w, 3 x 7.5w or 15w.

LISTING & RATINGS - CSA: Listed for wet locations.



ORDERING INFORMATION SELECT APPROPRIATE CHOICE FROM EACH COLUMN TO FORMULATE ORDER CODE. Refer to example below.

SERIES	WATTAGE	LAMP SOURCE	LENS	COLOR TEMP	LINE VOLTAGE	LUMINAIRE FINISH	OPTIONS
AOL	1 - 1 x 15w 2 - 2 x 7.5w 3 - 3 x 7.5w 4 - 2 x 15w 5 - 3 x 15w	LED - LED	C - Clear Prismatic Molded Borosilicate Glass Lens F - Frosted Prismatic Molded Borosilicate Glass Lens	2 - 2700K 3 - 3000K 4 - 4000K	120V 240V	BRZ - Bronze BLK - Black WHT - White CC - Custom Color	TR - Die Cast Aluminum Trim Ring, 19 1/2" Outer Diameter. Allows for recessed mounting of fixture PR20 - 20° Plastic Reflector PR40 - 40° Plastic Reflector PR40W - 40° Plastic Reflector, Wide PR60 - 60° Plastic Reflector NO - No Option
AOL	1	LED	F	2	120	BLK	NO

(EXAMPLE ORDER)

ORDER :
WLS-AOL

Approved By: _____ Project Name: _____

Location: _____ Date: _____

WLS LIGHTING SYSTEMS

1919 Windsor Place | Fort Worth, TX 76110 | 800.633.8711 | Fax: 817.735.4824 | www.wslighting.com

Consider the Impact!