



WLS LIGHTING SYSTEMS

ARS LED GARAGE/CANOPY SERIES



DIMENSIONS



A	B	Weight:
5.68	14.00	18 lbs
(144.22 mm)	(355.6 mm)	8.16 kg

SPECIFICATIONS

GENERAL DESCRIPTION - Ceiling applications from eight to eighteen feet for surface, box or pendant mount. Applications include parking garage, walkway or building canopies, corridors, tunnels, large stairwells and other interior applications with ambient 40 range of lumen packages and optical distributions are available making the ARS Series luminaire both versatile and functional.

CONSTRUCTION - Die cast aluminum housing features vertical fins for two directional airflow that maximizes heat dissipation and ensures long electrical component life and luminaire performance. LED light engines and electrical compartment are thermally isolated with an air gap for optimum component performance and long life. One piece molded silicone gasket ensures weather proof seal around each individual LED; Stamped stainless steel bezel provides mechanical compression to seal the optical assembly; 18L and 24L luminaires include finish (color) matching blanking bezel. Vandal resistant polycarbonate and low brightness acrylic shield accessories available

TESTING AND COMPLIANCE - Listed to UL 1598 for use in wet locations, 40 environments; Meets DesignLights Consortium (DLC) qualifications, Consult DLC website for more details: <http://www.designlights.org/QPL>; IP65.

ELECTRICAL - 120V-277V 50/60Hz, 54.4W, 57W or 86W, 700mA configurations. Drivers RoHS compliant and IP66. 0-10V dimming drivers. Lumens per watt > 92-102. Designed and certified for 40 driver/LED systems or -30 life and needs replacement

OPTIONS - Photcell (voltage Spec). Fusing. Motion Control (High/Low)

WARRANTY - Five year Limited Warranty.

ORDERING INFORMATION

SELECT APPROPRIATE CHOICE FROM EACH COLUMN TO FORMULATE ORDER CODE. Refer to example below.

SERIES	LED COUNT	DRIVE CURRENT	DISTRIBUTION TYPE	LINE VOLTAGE	LUMINAIRE FINISH
ARS	18L 24L 36L	70 - 700mA 83 - 833mA	5M - Type V Medium 5R - Type V Rectangle 5W - Type V Wide 4 - Type IV	42 - 4200K 51 - 5100K UL - 120-277V	BRZ - Bronze BLK - Black PLT - Platinum SLV - Silver WHT - White GRN - Green CC - Custom Color

ARS 18L 70 5M 42 UL BRZ
(EXAMPLE ORDER)

ORDER :
WLS-ARS



Made in the U.S.A. of U.S. and imported parts.
Meets Buy American requirements within the ARRA.

Approved By: _____ Project Name: _____

Location: _____ Date: _____

1919 Windsor Place ■ Fort Worth, TX 76110 ■ 800.633.8711 ■ Fax: 817.735.4824 ■ www.wlsighting.com

WLS LIGHTING SYSTEMS

Consider the Impact!