

SERIES	BEAM	WATTAGE	BALLAST	CCT	LENS	COLOR	MOUNTING	OPTIONS	ACCESSORIES	
FLL	F - Medium Flood, 100°H x 100°V, NEMA 7Hx7V I - Spot Flood, 27°H x 27°V, NEMA 4H x4V	37w	<b>U</b> - 120-277V <b>H</b> - 347/480V		C - Clear Flat Glass Lens P - Clear Flat Prismatic Lens* * Use with F Optics only	Z - Bronze C - Custom Color	KN - <sup>1</sup> /2" NPS Knuckle Included SF - Slipfitter	SF - Single Fuse DF - Double Fuse SP - Surge Protection NO - No Options	FLPTFZ - Die-cast Post Top Fitter for 23/8"   to 31/2" Poles, Bronze Powdercoat Finish,   Three ½" Coin Plugs.   FLSTK - Heavy Duty Ground Stake,   Built-in Wiring Compartment with 1/2" NPS   Threaded Fitting, Black Plastic.   FL45GSZ - Glare Shield, Aluminum,   Bronze Powdercoat Finish, Includes   Hardware.   FL45LG - Clear Polycarbonate Vandal   Resistant Guard, Includes Hardware.   FL45WG - Wire Guard, Stainless Steel,   Includes Hardware.   NA - No Accessories	
FLL ORDE WLS-		<b>1X37</b> ORDER)	U	5K	C	Z	KN	NO	NA	
roved By:				Proj	Project Name:				10 A.	
tion:				Date	Date:				WLS LIGHTING SYSTEMS	
Box 100	519 <b>F</b> o	rt Worth,	TX 76185	800.63	3.8711 "	Fax: 817.735.4	824 <sup>II</sup> www.wl	slighting.com	Consider the Impact	