


LHW SERIES LED SEMI-CUTOFF HOODED WALL PACK



DIMENSIONS



A	C	D
9" (229mm)	9" (229mm)	14¼" (362mm)

SPECIFICATIONS

HOUSING

Die Cast Hinged and Gasketed Aluminum Front Frame and Housing with ½" Coin Plugs. Nickel-Plated Stainless Steel Hardware. Photocell Adaptable.

LISTING & RATINGS

CSA: Listed for Wet Locations, ANSI/UL 1598, 8750 IP55 Sealed LED Compartment.

FINISH

Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

LENS

Tempered Clear Flat Glass Lens.

MOUNTING OPTIONS

Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box, or Use ½" Surface Conduit.

EasyLED LED

Aluminum Boards

WATTAGE

Array: 37.2w, System: 43.6w (250w HID Equivalent)

DRIVER

Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz; Dimmable Driver

WARRANTY

5-Year Warranty for -40°C to +40°C Environment.



Made in the U.S.A. of the U.S. and imported parts.
Meets Buy American requirements for ARRA.

Project Name: _____

Date: _____

Location: _____

Notes: _____

LHW SERIES LED SEMI-CUTOFF HOODED WALL PACK

ORDERING INFORMATION SELECT APPROPRIATE CHOICE FROM EACH COLUMN TO FORMULATE ORDER CODE.

Refer to example below.

SERIES	OPTICS	WATTAGE	DRIVER	COLOR TEMPERATURE	LENS	COLOR	OPTIONS
LHW	F Type IV	1X37 37w	U 120-277V H 347/480V	4K 4000K 5K 5000K	C Clear Flat Glass Lens	Z Bronze C Custom (Consult Factory)	SF Single Fuse DF Double Fuse SP Surge Protection PC1 Photocell, 120VAC PC2 Photocell, 250-305VAC BU Battery Backup, 90 Minutes

ORDER:

WLS-LHW	F	1X37			C		
---------	---	------	--	--	---	--	--

Example: WLS-LHW-F-1X37-U-4K-C-Z-SF

FOOTNOTES:

1 Consult your WLS sales person.



1919 Windsor Place
Fort Worth, TX 76110
800.622.8711

www.wslighting.com

Project Name: _____

Date: _____

Location: _____

Notes: _____

09 REV. 12/17

Specifications subject to change without notice.